

CX36230IL Technical Data

Features

| | |
|--------------------------|---|
| User group | Professionals |
| Power output | 3,6 kW |
| Control type | Controlled by a separate control unit |
| Installation location | Wall |
| Installation orientation | Vertically |
| Colour | Black |
| Main material | Steel |
| Ambient temperature min | 5°C |
| Ambient temperature max | 50°C |
| Use environment | Interior - dry area |
| Prime energy/fuel | Electric (high voltage 400V/230V 1/3N~) |

Measurements

| | |
|----------------------|--------|
| Control panel width | 85 mm |
| Control panel depth | 24 mm |
| Control panel height | 110 mm |

Weight

| | |
|-----------------|--------|
| Net weight (kg) | 1,8 kg |
|-----------------|--------|

Distances

Sensor cable length 5 m

Electrical

Electrical frequency 50/60 Hz

Electrical group options 230V~

Logistics

EAN 6410082614110

Electrical number (STK) 8261411

Customs tariff number EU 85371098

Customs tariff number RU 85371098

ETIM number EC000235

UNSPSC number 43201542

Product unit (pcs, meters etc.) PCS

Sales unit pcs

Quantity 1

Packaging materials Cardboard

Package height 90 mm

Package width 220 mm

Package depth 420 mm

Gross weight 2 kg